

PRODUCT DATA SHEET

1 Product:

Code: ABM402

Name: Bench Top Meter Cond/TDS/Temp

2 Features:

- Advance Microprocessor based design
- Rugged ABS housing and splash-proof keyboard.
- Large LCD display for multi-parameter display simultaneously.
- Built-in ATC (Automatic Temperature Compensation).
- Advance Storage / Memory function with USB Connectivity.
- Computer Data Transfer USB Connectivity.



3 Specification:

Model	ABM402			
Parameter	Conductivity	TDS	Salt	Temp
Range	0 to 100 mS/cm	0 to 66.0 ppt	0 to 50 ppt	0 to 110 Deg C
Accuracy	1%	1%	1%	±0.2
Resolution	1µS	1 PPM	1 PPM	0.1 Deg C
Calibration	Conductivity - 0µS/cm, 84µS/cm, 1413µS/cm, 12.88mS/cm, 80mS/cm			
ATC	Yes (Built-in ATC (Automatic Temperature Compensation))			
Output	USB Connectivity with Windows Computer and Software (Provided)			
Sensor*	Conductivity & Temperature sensors included.			

4 Packing:

- Included**
- Meter: ABM402
 - Cond/TDS Sensor: AMECNLG
 - Temp Sensor: AMETEMP
 - Cond Solution: 1413µS/cm
 - Magnetic Stirrer: Stirrer with Speed Control and Electrode Holder