

RAKIRO BIOTECH SYSTEMS PVT LTD

R-466, TTC Industrial Area, MIDC Rabale, Navi Mumbai - 400701 Tel No. +91-022-47804040

Email:-sales@rakiro.net

Doc No: TDSWTA100

Date: 01-04-2024

Type: UDAAQ

Product Code: WTA100

PRODUCT DATA SHEET

1 INFORMATION

Product Code: WTA100
Product Name: Polymeric Dispersant

Application: Cooling System Treatment

2 **DESCRIPTION**

UDAAQ A 100 is a synthetic organic anti-foulant which inhibits the deposition of fouling materials on the heat transfer surfaces. Fouling caused by dead microbiological growth, phosphates, silicates, metallic oxides silt and other air-borne materials can be eliminated. UDAAQ A 100 keeps surfaces clean, maintains a high rate of heat transfer and aids the formation of corrosion inhibitor film.

3 **SALIENT FEATURES**

Improves heat transferPrevents and removes depositsReady-to-use-liquidChemically stableEasy to handle and feedkeep surface clean

Easy to handle and feed keep surface clean

Effective at low dosages Keeps tower basin clean

4 ANALYTICAL DATA

Appearance : Pale yellow colour hazy liquid

pH : 6.0 To 8.5

Density : 1.0 To 1.1

5 **HANDLING INSTRUCTIONS**

Keep the container away from direct heat & sunlight. Keep the container closed when not in use. The product should not be swallowed and prolonged contact with the skin should be avoided. Should it come in contact with the eyes, flush with clean, cold water and get medical attention.

6 RECOMMENDED DOSAGE

An dosage of 50 PPM is recommended but this dosage is to be adjusted in such a way that it should give protection to the system, while being economical. Dosage might vary depending on the parameters viz. the temperature of the system, the type of metal, the characteristic of the makeup water.