

Bench Top pH/TDS/DO Meter

SKU: ABM405 | Range: pH 0 - 14 / TDS 0-66000 PPM / DO 0-20 PPM

The AQUASOL DIGITAL Bench Top Multi-Parameter Meter is a next-generation, high-performance laboratory instrument designed for comprehensive water quality analysis. This advanced system enables accurate measurement of pH, ORP (Redox), Conductivity, TDS, Salinity, Dissolved Oxygen (DO), Oxygen (O₂), and Temperature—all in a single compact unit. Engineered with advanced microprocessor technology, the instrument delivers fast response, exceptional stability, and highly precise results, making it ideal for water and wastewater treatment plants, pharmaceuticals, chemical industries, aquaculture, environmental monitoring, food & beverage, and research laboratories. Supplied with an magnetic stirrer, the meter ensures uniform sample mixing during analysis, significantly improving measurement accuracy, repeatability, and response time, especially for critical parameters like dissolved oxygen. Designed for maximum flexibility, this multi-parameter analyzer allows users to seamlessly switch between parameters by connecting the respective electrodes. The unit is supplied with all essential sensors (pH, conductivity/TDS, DO, temperature), while the ORP electrode is optional, provided



KEY PRODUCT FEATURES

- Advance Microprocessor based Design
- Convenient with Splash proof keyboard
- Stable Platform with Electrode holder
- Large LCD display with Backlight.
- Built in ATC (Automatic Temperature Compensation).
- Advance Storage/Memory function.
- Magnetic Stirrer Provided
- USB Connectivity with Software

TECHNICAL SPECIFICATIONS

Model - ABM405

pH Range - (-) 2.00 to 16.00

pH Accuracy - 1%

pH Resolution - 0.01 pH

ORP Range - \pm 1999 mV

ORP Accuracy - 2%

ORP Resolution - 1 mV

Conductivity Range - 0 to 100 mS/cm

Conductivity Accuracy - 1%

Conductivity Resolution - 1 μ S

TDS Range - 0 to 66.0 ppt

TDS Accuracy - 1%

TDS Resolution - 1 PPM

Salt Range - 0 to 50 ppt

Salt Accuracy - 1%

Salt Resolution - 1 PPM

DO Range - 0 to 20.00 mg/L

DO Accuracy - 2%

DO Resolution - 0.01 mg/L

O₂ Range - 0 to 200.0 %

O₂ Accuracy - 2%

O₂ Resolution - 0.01

Temp Range - 0 to 110 Deg C

Temp Accuracy - \pm 0.2

Temp Resolution - 0.1 Deg C

Stirrer - Magnetic Stirrer Provided

ATC - 0 to 100 °C

Sensor (Default) - pH, TDS, DO and Temperature Sensor is provided along with a meter.

To measure ORP purchase separate electrode.